

RM-790 9-Bay Vertical Disk Array Chassis 4U



Features:

- * Industrial standard 19" 4U metal chassis
- * 9x5.25" open bays ideal for RAID applications + 2x3.5" hidden bays, 20.25" deep

Options:

- * CABLE: 9-plug SCSI LVD cable, External cable/terminator
- * 68-pin LVD, SCA LVD, 3-in-1 SCA box (Data Carriers) for RAID application
- * Black exterior
- * 50 pin or 68 pin W/UW/U2/ LVD SCSI cables
- * External SCSI cables and terminators
- * Hot-Swappable mobile racks (Data carriers) for W/UW/U2/ LVD SCSI HDD
- * Alarm for fan and temperature

Specifications:

- * Drive Bays: 9 x 5.25" open bays + 2 x 3.5" hidden bays
- * Air-flow volume: 1.8 CBM/min.
- * Operational temperature range: 0 ~ 55 ° C
- * Power & HDD LED's
- * Power supply (All UL/CSA/TUV certified):
- * AT Power-PS/2 300/400w or 2x300w(RPI-4300)/2x400w Redundant Hot-Swappable
- * Dimensions: 16.8" x 17.7" x 7" (W x D x H)
- * Gross weight: 35 lbs. (w/ PS2 power supply)