

# RM-828 19" Rackmount Chassis 7U

## Features:

- \* For main board of single board 20/14 full size or half size or ATX 12"x13" or 12"x9.6" or Micro ATX 9.6"x9.6" or Mini-ITX 6.6"x6.6"
- \* 14 bays
- \* 4 front keyboard connectors for multi-system applications (converter cable optional)
- \* 7 built-in cooling fans
- \* Lockable access door
- \* Adjustable hold down clamps
- \* Removable mainboard cage for easy installation and maintenance
- \* Space available for 20 full length slot cards
- \* 3 x 8cm intake cooling fans in front and
- \* 4 x 8cm intake cooling fans in the center
- \* Washable filter

## Options:

- \* Black exterior
- \* Single board computer cards
- \* 14/20-slot Industrial Passive backplane board
- \* Removable racks ([Data Carriers](#)) for SATA/IDE/SCSI HDD



## Specifications:

- \* Drive Bays: 6 x 5.25" open, 2 x 3.5" open, 6 x 3.5" hidden
- \* For main board of single board 20/14 full size or half size or ATX 12"x13" or 12"x9.6" or Micro ATX 9.6"x9.6" or Mini-ITX 6.6"x6.6"
- \* Operational temperature range: 0 ~ 55 ° C
- \* Power supply (Options):
  - PS/2 power supply 300W/400W/500W~1000W
  - Mini redundant power supply 300W/400W/500W
- \* Dimensions: 19" x 22.5" x 12.25" (W x D x H)
- \* Gross weight: 64lbs. (w/ PS2 power supply)