

**TWIN OUTPUT**

WT-1215-TB : 12V/15A

**TWIN OUTPUT**WT-1225-TB : 12V/25A  
WT-2415-TB : 24V/15A**TWIN OUTPUT**WT-1245-TB: 12V/45A  
WT-2425-TB: 24V/25A**THREE OUTPUT**WT-1225-TC : 12V/25A  
WT-2415-TC : 24V/15A**THREE OUTPUT**WT-1245-TC: 12V/45A  
WT-2425-TC: 24V/25A

## Technical Data:

Article number	WT-1215-TB	WT-1225-TB WT-2415-TB	WT-1245-TB WT-2425-TB	WT-1225-TC WT-2415-TC	WT-1245-TC WT-2425-TC	
Battery Connection:	One plus 1A output for : Starter battery	two	two	Two plus 1A output for : Starter battery	three	
Input voltage range	115V 230V	98 -132VAC / 50-60Hz 207-253VAC / 50-60Hz				
Charging end voltage:	12V 24V	14.4V/14.8V	14.4V/14.8V 28.8V/29.6V	14.4V/14.8V 28.8V/29.6V	14.4V/14.8V 28.8V/29.6V	
Economic charging voltage	12V 24V	13.8V	13.8V 27.6V	13.8V 27.6V	13.8V 27.6V	
Max. battery capacity:	12V 24V	150Ah	300Ah 200Ah	500Ah 300Ah	300Ah 500Ah 300Ah	
U0 phase limitation:	4h or 8h					
Max. charging current	12V 24V	15A	25A 15A	45A 25A	25A 15A	
Operating temperature	0°C - 50°C					
Dimensions (mm):	200 x 60 x 260	240 x 77 x 310	230 x 108 x 325	240 x 77 x 310	230 x 108 x 325	
Fuse	115V 230V	T4A/250V T2A/250V	T8A/250V T4A/250V	T12A/250V T6.3A/250V	T8A/250V T4A/250V	T12A/250V T6.3A/250V
Weight		2.4 kgs	3.5 kgs	5.05 kgs	3.5 kgs	5.05 kgs
Protection	1. Short circuit protection 2. Overload protection 3. Reverse polarity protection 4. Overtemperature protection					

## Features :

- 3 stages charging.
- Remote control: Accessories No. 900-RC.
- Temperature sensor: Accessories No. TF-500.
- External dip switch: Voltage selectable, charging timer selectable.
- Sleeping mode: Fan stops working.
- No "trickle charge" to be bill off electrolyte.
- Design for installation anywhere on board.
- Maintains batteries in perfect condition and prolong their useful life.

OEM &amp; ODM are welcome.



**Accessories:**

**900-RC Remote Control**



**TF-500 Temperature Sensor**

