



ELECTRICAL PROPERTIES:

1. 100% OPEN SHDRT MIS-WIRE TEST
2. Contact Resistance: 100ohm
3. Insulation Resistance: 5Mega ohm
4. HI-Pot:300V DC/10ms

Pin Assignment

Conn.t.1	Conn.t.2	COLOR
1	1	RED
2	2	WHITE
3	3	GREEN
4	5	BLACK
SHELL	SHELL	BRAID

5	FERRITE CORE L25mm*1DØ5.6*DDØ12mm	1	PCS
4	P.V.C MOLDING SSP COLDR: BLACK	9	
3	MINI USB SPIN B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	Set
2	USB A TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	Set
1	CABLE: UL2725 28/1P+28#/2C+AEB REV 2.0 JACKET COLDR: BLACK DD: 3.5±0.1mm		MM
ND.	DESCRIPTION	Q'TY	UNITS
A	CABLE REV2.0 USB AM TD MINI USB SP L:1.83M W/CORE		
REV.	DESCRIPTION	DATE	

UNLESS OTHERWISE SPECIFIED TOLERANCE

ANG: ±5°
 ±0.5
 0, ±0.3
 .00 ±0.2

SCALE: NONE UNIT: MM

DRAWN Xing Fa 07/12/5
 CHECKED Eric 07/12/5

APPROVED

康熙-USB2-A5MB-183-C

PRODUCT NO. USB2-A5MB-183C

FILE NAME: USB2-A5MB-183C

COMIX