



P1	P2
3	3
1	1
2	2
6	6
4	4
5	5
9	9
7	7
8	8
12	12
10	10
11	11
18	18
15	15
16	16
19	19
13	13
SHELL	SHELL

3	<TMDS Data 2->
1	<TMDS Data 2+>
2	<TMDS Data 2 Shield>
6	<TMDS Data 1->
4	<TMDS Data 1+>
5	<TMDS Data 1 Shield>
9	<TMDS Data 0->
7	<TMDS Data 0+>
8	<TMDS Data 0 Shield>
12	<TMDS Clock ->
10	<TMDS Clock +>
11	<TMDS Clock Shield>
18	<+5V Power>
15	<Ground>
16	<DCC Clock>
19	<DCC Data>
13	<Hot Plug Detect>
SHELL	SHELL

ELECTRICAL TEST:

1. CURRENT RATING: DC 0.5A
2. WITHSTANDING VOLTAGE: DC 300V
3. INSULATION RESISTANCE:5Mohm
4. CONDUCTIVE RESISTANCE:100ohm

5	CORE:28.5*ø16.0*ø9.5	PCS	1
4	Aluminum Alloy HODD<BLACK>	PCS	2
3	SSP PVC MOLDING BLACK IN COLOR	PCS	
2	HDMI A MALE SHELL PLATED:GOLD CONTACT:G/F	PCS	2
1	CABLE UL20276 28AWG/4P+28AWG/1P+28AWG/5C+AB JACKET BLACK DD:7.0mm	PCS	1
No.	DESCRIPTION	UNIT	Q'TY
A	HDMI CABLE A-TYPE MALE TO A-TYPE MALE		
REV.	DESCRIPTION		

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG. ±5°
 0 ±0.5
 .00 ±0.3
 .00 ±0.2

COMIX

DATE	07/12/5	DRAWN	Xing Fd	07/12/5	DRAWN NAME:	康熙-HDMI-MMG-ABK-1.8-C
APPROVED		CHECKED	Eric	07/12/5	PRODUCT NO.	
SIZE	A4	REV.	A	FILE NAME:		