

HDMI (HDBaseT) CAT5 Extender Series

ITEM NO.: HE02 HDMI CAT5 Extender With RS232 & IR over Single CAT5 cable




HE02 HDMI CAT5 Extender is using only one cost effective CAT5E/6 cable to extend your HDTV display up to 100 meters at 1080p. With Bi-directional RS232 and IR function to delivers significant value to the entire home and commercial entertainment system.

HE02 HDMI CAT5 Extender With RS232 & IR over Single CAT5 cable

Features:

- Extends HDMI with control signal over one CAT5/5e/6 cables.
- Controls signals including RS232 and IR remote control.
- Uncompressed high definition video up to 1080p@60Hz@48bits and 3D and 4K*2K capable.
- Max. Data Rate- 10.2 Gbps.
- HDMI 1.4 and HDCP compliance.
- Bi-Directional IR function.
- Bi-Directional RS232 interface – commands and data can flow in both directions via RS232, allowing status requests and control of the destination unit.
- Audio transmission support Dolby TrueHD, DTS-HD MA.
- Transmission range up to 100 meters at 1080p resolution.

Installation view:




Cable:

Link cable recommend use high quality Cat.5e, Cat.6, Cat.6a, Cat.7 UTP / STP or FTP cable. Poor quality cable or network connection or improper construction will cause unstable connection, video or sound disruptions, picture noise appears.

HDBaseT Distance chart by different cable:

| Cable Type | Range | Pixel Clock Rate | Video Data Rate | Supported Video |
|--------------|-------|------------------|------------------------------|---|
| CAT5e / CAT6 | 100m | <=225Mhz | <=5.3Gbps (HD Video) | Up to 1080p 60Hz 36 bits |
| | 70m | >225Mhz | >5.3Gbps (Ultra HD Video) | 1080p 60Hz 48bits 1080p 60Hz 3D, 4K x 2K 30Hz |
| CAT6a / CAT7 | 100m | | | |

If connection through the wall socket, the cable length must be less than 5 meters between HDMI extender and wall jack, as shown in the drawing below:



10/100Mbps network connection using general CAT5e cable and working distance up to 100M.

Low-power Mode:

When there is no HDMI video signal input, or TV is not connected or power off, this product will enter a low-power mode to save power consumption; Under a low power mode still provides Ethernet, RS-232(Max. 9600bps), IR, CEC of signal transmission.

RJ45 Define:

Video Link (TIA/EIA-568-B)

- | | |
|-----------------|---------|
| 1. Orange-white | DATA0 + |
| 2. Orange | DATA0 - |
| 3. Green-white | DATA1 + |
| 4. Blue | DATA2 + |
| 5. Blue-white | DATA2 - |
| 6. Green | DATA1 - |
| 7. Brown-white | DATA3 + |
| 8. Brown | DATA3 - |

HE02 LED Indication :


| | | |
|----|-------|-------------|
| ON | GREEN | Power |
| IR | BLUE | IR Receive |
| IR | RED | IR Transmit |

RJ45 LED Indication :


| | | |
|-------|-------|------------------------|
| VIDEO | GREEN | ON : HDBaseT linking |
| | | Flash : Low Power Mode |

Panel view:

HE02T



HE02R



Caution:

1. The wiring must away from any equipment with electromagnetic wave, i.e.: mobile phone, microwave, radio equipment, fluorescent lamp, high voltage power lines.
2. The cable must pull in straight to avoid any crosstalk interference and the transmission stability.
3. This device HDBaseT port is not general Ethernet signal; do not connect with Network devices to avoid damage.
4. IR transmitter do not put near from receiver to avoid mutual interference.

Package Include:

HE02T HDM Transmitter x 1 pcs
 HE02R HDMI Receiver x 1 pcs
 IR Emitter Cable x 2 pcs
 IR Receiver Cable x 2 pcs
 Mounting Screw pack x 2 bags
 Power Adapter x 2 pcs

Specification:

| ITEM | HE02T | HE02R |
|-------------------|---|-----------------------|
| HDMI Connector | 1080p / 60Hz / 48 bits · 3D · 4K x 2K | |
| HDMI Video | 7.1 LPCM 192KHz · Dolby TrueHD · DTS-HD MA | |
| Distance | 100M (Max) | |
| HDMI Connector | HDMI Type A | |
| RS-232 Connector | DB9 Female | DB9 Male |
| HDBaseT Connector | RJ45 x 1 | |
| RS-232 Baud Rate | Up to 115200 bps / Full Duplex | |
| IR Carrier | 30~60KHz , T : ± 15° , R : ± 55° , 5M / Bi-directional | |
| Power Supply | DC 5V 2AMP | |
| Power Consumption | Max 3W · Low Power 0.8W | Max 6W · Low Power 1W |
| Temperature | Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up to 95% | |
| Dimensions | 88 x 130 x 30 | |
| Weight | 255 | 270 |



Rev. C