

VGA & USB, AUDIO, RS232, IR CAT5 Extender

ITEM NO.: VKM03 VGA & USB with Stereo Audio, RS232, IR CAT5 Extender

The VKM03 VGA, USB with Stereo Audio, RS232,IR CAT5 extender design for extends all signal over one CAT5 up to 150 meters, with local VGA monitor output. It provides superior video quality up to 1920 x 1080 resolution, and using cost effective Cat5e cable, instead of VGA, audio, RS232 cables, for a easy, neater and reliable installation. It is optimized for applications at digital signage, home network integration, industrial control, security, and KVM extension.

Features:

- Extend VGA, stereo audio, RS232, IR and USB signals over one CAT5E/CAT6 cable.
- USB port support USB 2.0, USB 1.0 & USB 1.1
- Transmitter unit built in VGA loop output.
- Receiver unit with 4 ports USB devices, to extend USB 2.0 peripheral devices, such as flash disk, hard disk, keyboard, mouse, etc.
- Supports up to 1920 x 1080.
- Transmission range up to 150 meters.
- Plug and play for easy operation.
- Perfect for control remote machines and security monitoring systems, digital signage application.
- Optional model: SR01 signal repeater for longer distance application.



Optional Model: order separately

SR01 Signal Repeater


- Extend data signal over CAT5 cable.
- Application for UE02 USB CAT5 Extender up to 240 meters.
- Application for VKM03 VGA+USB CAT5 Extender up to 240 meters.
- Work with SR01, to extend VKM03 VGA, USB, RS232, audio signal only, without IR function.
- Built in LED status indication.
- External power required.
- Plug and play for easy installation.

Work with VKM03 CAT5 Extender:




Panel View:

Transmitter



Receiver



Cable:

Video Link cable using high quality CAT5E UTP/STP/FTP or CAT6 UTP cable.

RJ45 Define:

Link Cable (TIA/EIA-568-B)

- | | |
|-----------------|----------|
| 1. Orange-white | Data 1 + |
| 2. Orange | Data 1 - |
| 3. Green-white | Data 2 + |
| 4. Blue | Data 3 + |
| 5. Blue-white | Data 3 - |
| 6. Green | Data 2 - |
| 7. Brown-white | Data 4 + |
| 8. Brown | Data 4 - |

LED Indication Status:

Power	On (power)
Link	Flash (under linking)
	On (linking)

RJ-45

Green	Flash (Data transmission)
Orange	On (linking)

Note: IR receiving angle ± 55 degree, emitting angle 30degree , distance reach to 3-5 meters.

Specification:

ITEM NO.	VKM03T	VKM03R
Support Resolution	Up to 1920 x 1080 @ 85 Hz	
Transmission Distance	Up to 150 (Max)	
Video Input Signals	RGB Analog (75 Ω , 0.7Vp-p) Sync Signal H/V Separated (TTL)	
VGA Connector	15-pin D-Sub Female x 1	15-pin D-Sub Female x 2
USB Connector	B-Type x 1	A-Type x 4
RS232 Connector	DB9(Female) x 1	DB9(Male) x 1
Audio Connector	3.5 Phone Jack x1	3.5 Phone Jack x1
IR Connector	3.5 Phone Jack x1	x
Link Connector	1 x RJ-45	
Power Supply	DC5V 2Amp	DC5V 2Amp
Power Consumption	1.1Amp	1.1Amp
Temperature	Operation: 0 to 55 $^{\circ}$ C, Storage: -20 TO 85 $^{\circ}$ C, Humidity: up to 95%	
Dimensions W x H x D mm	125*120.5*30 (mm)	125*120.5*30 (mm)
Weight g	350g	350g

RoHS CE FC