



SH-6650-19-4(108D/116D)-EN-B-AC

SH-6650

Specification

All Modularized Design

19" TFT LCD Module (Support Multi-Sync)

8,16 PORT KVM switch Module (USB + PS/2)

8 Language Keyboard Module

Easy Change Modular. (Tooling loss Design.)

One person Quick and easy installation.

Sun Micro System supported.

Can Use for 520mm~980mm Cabinet Rack

*Heavy-duty steel electroplated for chassis

*Only 1U **4IN1** Drawer(LCD, KB, MOUSE,KVM Switch)

Keyboard Modules

*105 key Keyboard, compatible to IBM PC/AT, PS/2 keyboard, supports Windows function keys & Sun Micro System Function Key (Germany, English, French, Italian, Spanish, Japanese, Chinese, UK....optional)

*PS/2 Touchpad (Microsoft mouse compatible with PS/2 mouse interface)

Full Wheel Mouse emulation. Left, middle and right button emulation.

TFT LCD Modules

*19" TFT LCD Panel Module

-Built-in 7 languages OSD controls

-Resolution 1280 x 1024

-Backlight lifetime: 50,000 hrs.

-Sun Micro System Multi-Sync Supported.

-Sun Micro System 1152x900 Resolution Supported.

-Automatic flat panel shut-off when monitor is in the closed position, or no signal input.

KVM switch Modules (USB+PS2)

8/16 Port KVM switch (108D/116D)

- One USB-PS/2 console controls 8 /16 computers
- Cascade up to 2 levels - control up to 128/256 computers
- Dual Interface - supports computers with PS/2 or USB keyboards
- Multiplatform support - Windows 2000/XP/Vista/Windows 7, Linux, Mac, and Sun
- Supports multimedia USB keyboards for PC, Mac and Sun
- Auto PS/2 and USB interface detection
- USB or PS/2 keyboard and mouse emulation - computers boot even when the console focus is elsewhere
- Supports VGA resolution up to 2048 x 1536 VESA DDC1/2B compatible
- Computer selection via front panel pushbuttons, hotkeys and multilingual on-screen display

(OSD) menu

- Three level password securities - only authorized users' view and control computers; up to four users and an administrator with a separate profile for each, password for each port.
- Auto Scan feature for monitoring user-selected computers
- Hot pluggable - add or remove computers without having to power down the switch
- Buzzer on/off via hotkey and OSD
- Firmware upgradeable
- No software installation required
- Supports Two PS/2 Console.
- Designed for desktop or rack mount (19" system rack, 1U)

			108D	116D
Computer Connections	Direct		8	16
	Max.		128 (via Cascade)	256 (via Cascade)
Port Selection			OSD, Hotkeys, Pushbuttons	
Connectors	Console Port	Keyboard	1 x USB & 1 PS/2	
		Mouse	1 x USB & 1 PS/2	
	KVM Ports	Keyboard	8 x HD-15 Female (Black)	16 x HD-15 Female (Black)
		Mouse		
		Video		
Power	1 x DC Jack (DC 12V)			
Emulation	Keyboard/Mouse	PS/2, USB		
Video			2048 x 1536; DDC2B	
Scan Interval			1-255 Seconds	

Power Supply Modules

*Universal 100~240V AC input,12V DC output power adapter Module
(UL/c UL/TUV/CE/FCC/CCC)

*SH-SDD30-48S12:-48V DC input adapter Optional

*SH-SDD30-24S12:24V DC input adapter Optional

Cable

*CB-K15P-180: UL-2919 rated 3-in-1 cables set with VGA, keyboard (PS/2), Mouse (PS/2) 1.8M (3M,5M,10M,20M, 30M Optional).

*CB-K15U-180: UL-2919 rated 3-in-1 cables set with VGA, keyboard & Mouse (USB) 1.8M (3M,5M,10M,20M, 30M Optional).

Color

*Available in black. (Colors available for OEM)

Environmental Condition:

Operation Temp.: 0~50 degree C

Storage Temp.: -20~60 degree C

Humidity: 10~90%

Dimensions

W.482mm x **L.**610mm x **H.**44mm

N.W. 18 KGS

G.W. 22 KGS

CUFT. 3.3

The specification and pictures are subject to change without notice.