

# ST-1041SS

## 4-Bay 2.5" SAS/SATA HDD Backplane Modules in 1 x 5.25" Bay



Support 2.5" SATA/SAS HDD upto 15mm in height  
4 x 2.5" SATA/SAS HDD in 1 x 5.25" Bay



**ST-1041SS** (HDD not included)



**HDD tray** (HDD not included)

SATA HDD with cover

SAS HDD w/o cover

### Features:

- \* Interface: Support SAS, SATA-I, SATA-II
- \* Support 4 X 2.5" SAS & SATA Hard Disks  
(\*for SAS, support SAS primary channel only)
- \* All aluminum material solid construction
- \* Tri-angle keylock tray design for HDD tray
- \* Anti-shock protection HDD tray design
- \* Cableless HDD connection
- \* Support Windows/Mac/Linux
- \* Support RAID 0,1,10, 5,JBOD Functions (Need an optional SAS or SATA Raid Controller)
- \* Support 2.5" HDD thickness from 9.5 upto 15mm
- \* Indication : 1 x twin color LED for Power & HDD
- \* Support host SAS 3Gb/s 、 SATA 3Gb/s
- \* LED for Power & access blinking
- \* Switch for LED ENABLE or DISABLE
- \* Air-ventilation holes for best heat sink
- \* With 15Pin Power x 1 and 7Pin Signal connectors x 4
- \* Cooling fan : 2 X 4cm(4020) fan
- \* Dimension : 175(L) x 146(W) x 42(H)mm
- \* Net Weight : 0.8 kg, Gross weight: 1.3 Kgs



**Anti-shock and keylock design**

Model No.:	ST-1041SS
Interface	SAS, SATA-I, SATA-II For SAS, support primary channel only
Form factor	1 X 5.25" Bay for 4 x 2.5" HDD(SSD)
HDD Tray	4 x removable tray with keylock
Material	Aluminum body/metal trays/plastic cover
Raid Support	0,1,10,5,JBOD(*need extra Raid controller)
Power	1 x standard 15pin
Cooling fan	4cm(4020) Cooling fan x 2
LED Switch	LED "Enable" or "Disable"
LED x 1 (for each tray)	Conductive LED indicating Power on:Solid blue /Access:purple blinking
Handle/Lock	Tri-angle keylock for each HDD tray
Dimension	175(L) x 146(W) x 42(H)mm
Weight	0.8 kg(net weight) 1.3(gross weight)



**ST-1041SS(rear)**